

View Online at <https://aerobasegroup.com/nsn/5950-01-283-9123>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.980 inches single mounting facility single center group and 1.020 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.850 inches single mounting facility single center group and 0.890 inches single mounting facility single center group

Frequency Rating:

360.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 1.350 inches and 1.390 inches

Body Width:

Between 1.290 inches and 1.330 inches

Body Height:

Between 1.230 inches and 1.270 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

0.3 amperes ac single component single secondary

Winding Operating Voltage:

40.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0