## NSN 5950-01-284-6742

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-284-6742

| Reliability Indicator:  |
|---|
| Not established   |
| Turn Quantity:  |
| 5 single component all winding  |
| Mounting Hole Diameter:   |
| 0.175 inches single group   |
| Inductance Rating:  |
| 18.00 microhenries single component all winding and 27.00 microhenries single component all winding |
| Frequency Rating:   |
| 1.0 kilohertz single component  |
| Body Length:  |
| 0.546 inches  |
| Body Outside Diameter:  |
| 0.866 inches  |
| Winding Quantity:   |
| 2 single component  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 1 single group  |
| Mounting Method:  |
| Unthreaded hole single group  |
| Rating Method:  |
| Electrical single component all winding and winding turns single component all winding              |
| Features Provided:  |
| Tinned wire leads   |
| Winding Conductor Size:   |
| 0.04526 inches american wire gage single component all winding                                      |
| Winding Operating Current:  |
| 7.0 amperes dc single component all winding   |
| Dc Resistance Rating In Ohms:   |
| 0.010 single component all winding  |
| Terminal Type And Quantity:   |
| 4 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |