

View Online at <https://aerobasegroup.com/nsn/5950-01-285-1314>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Impedance Rating In Ohms:

5000.0 single component all secondary

Frequency Rating:

30.0 hertz single component and 15.0 kilohertz single component

Maximum Transformer Power Rating:

1.6 milliwatts single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 1.563 inches and 1.625 inches

Body Width:

Between 1.563 inches and 1.625 inches

Body Height:

Between 2.250 inches and 2.375 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Test Data Document:

49956-g104191 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0