## NSN 5950-01-287-4308

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-287-4308

**Reliability Indicator:** 

Not established

**Overall Length:** 

Between 2.937 inches and 3.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.281 inches single mounting facility single center group and 2.297 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

1.843 inches single mounting facility single center group and 1.859 inches single mounting facility single center group

**Overall Height:** 

Between 4.375 inches and 4.687 inches

**Overall Width:** 

Between 2.500 inches and 2.625 inches

Frequency Rating:

50.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

**Winding Shielding Method:** 

Internal shield grounded to core single component

**Maximum Operating Temp:** 

130.0 degrees celsius

**End Application:** 

Control panel

**Inclosure Type:** 

Hermetically sealed

**Mounting Facility Quantity:** 

4 single group

**Mounting Method:** 

Threaded stud single group

**Winding Function And Quantity:** 

1 primary single component and 2 secondary single component

**Thread Size:** 

0.164 inches single group

**Winding Operating Current:** 

2.16 amperes ac single component all secondary

Winding Operating Voltage:

28.00 ac volts single component all secondary

**Thread Series Designator:** 

Unc single group

**Terminal Type And Quantity:** 

6 wire hook

Shelf Life:

N/a

## NSN 5950-01-287-4308

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0