NSN 5950-01-287-9248

Reactor - Page 1 of 2

Demilitarization: Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5950-01-287-9248

View Online at https://aerobasegroup.com/nsn/5950-01-287-9248
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Inductance Type:
Fixed
Inductance Rating:
125.00 microhenries single component all winding
Frequency Rating:
10.0 kilohertz single component
Body Length:
0.415 inches
Overall Diameter:
0.630 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
2 single component
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Electrical single component all winding
Winding Operating Current:
1.86 amperes dc single component all winding
Dc Resistance Rating In Ohms:
0.125 single component all winding
Special Features:
Magnetically shielded
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 wire lead
Specification Data:
81349-mil-t-27/356 government specification
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-01-287-9248

Reactor - Page 2 of 2



Fiig:

A058b0