NSN 5950-01-290-0122

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-290-0122
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Inductance Type:
Fixed
Inductance Rating:
2.00 millihenries single component all winding
Frequency Rating:
10.0 kilohertz single component
Body Length:
0.635 inches
Overall Diameter:
0.950 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
2 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component all winding
Thread Size:
0.138 inches single group
Winding Operating Current:
950.0 milliamperes dc single component all winding
Dc Resistance Rating In Ohms:
1.000 single component all winding
Special Features:
Magnetically shielded
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single group
Terminal Type And Quantity:

81349-mil-t-27/356 government specification

4 wire lead

Specification Data:

NSN 5950-01-290-0122

Reactor - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0