NSN 5950-01-290-2391

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-290-2391

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 54.0 millimeters single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 40.0 millimeters single mounting facility single center group **Mounting Slot Width:** 4.0 millimeters single group **Frequency Rating:** 45.0 hertz single component and 450.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component **Body Length:** 70.0 millimeters Maximum Operating Temp: 110.0 degrees celsius **End Application:** 6625-01-255-4547 **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Slot single group Winding Function And Quantity: 2 primary single component and 3 secondary single component Winding Operating Current: 1.4 amperes dc single component 2nd secondary Winding Operating Voltage: 21.00 dc volts single component 3rd secondary **Terminal Type And Quantity:** 13 wire lead Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A058b0