NSN 5950-01-290-8844

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-290-8844

| _ | | | | | | | | | |
|---|----|----|----|-------|------|-----|----|------|---|
| D | ام | ia | hi | liŧ√. | , In | di | 00 | tor: | ı |
| ı | CI | ıa | vi | IILV | | ıuı | uа | LUI. | |

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.615 inches single mounting facility single center group and 2.635 inches single mounting facility single center group

Mounting Hole Diameter:

0.218 inches single group and 0.224 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.470 inches and 3.530 inches

Body Width:

Between 2.970 inches and 3.030 inches

Body Height:

2.500 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

250.0 milliamperes ac single component single primary

Winding Operating Voltage:

120.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5950-01-290-8844

Power Transformer - Page 2 of 2



Fiig:

A058b0