

View Online at <https://aerobasegroup.com/nsn/5950-01-291-0629>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.140 inches single mounting facility all center groupings and 1.160 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.615 inches single mounting facility all center groupings and 0.635 inches single mounting facility all center groupings

Mounting Hole Diameter:

0.178 inches single group and 0.198 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Two phase to three phase single component

Transformer Winding Connection Type:

Scott

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 2.525 inches and 2.555 inches

Body Width:

Between 0.970 inches and 1.000 inches

Body Height:

0.905 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

125.0 milliamperes ac single component all primary

Winding Operating Voltage:

6.00 ac volts single component all primary

Terminal Type And Quantity:

11 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0