

View Online at <https://aerobasegroup.com/nsn/5950-01-291-0802>

Reliability Indicator:

Not established

Overall Length:

5.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Overall Height:

4.750 inches

Overall Width:

4.000 inches

Mounting Hole Diameter:

0.190 inches single group

Frequency Rating:

45.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Maximum Operating Temp:

80.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Winding Operating Current:

3.0 amperes dc single component 1st secondary

Winding Operating Voltage:

9.00 ac volts single component 4th secondary and 18.00 ac volts single component 4th secondary

Special Features:

2 primary windings, 5 secondary windings; all output currents are shown rectified

Terminal Type And Quantity:

24 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0