## NSN 5950-01-291-0802

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-291-0802

Reliability Indicator:
Not established
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.000 inches single mounting facility single center group
Overall Height:
4.750 inches
Overall Width:
4.000 inches
Mounting Hole Diameter:
0.190 inches single group
Frequency Rating:
45.0 hertz single component and 440.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Maximum Operating Temp:
80.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
2 primary single component and 5 secondary single component
Winding Operating Current:
3.0 amperes dc single component 1st secondary
Winding Operating Voltage:
9.00 ac volts single component 4th secondary and 18.00 ac volts single component 4th secondary
Special Features:
2 primary windings, 5 secondary windings; all output currents are shown rectified
Terminal Type And Quantity:
24 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-291-0802

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0