## NSN 5950-01-292-3379

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-292-3379

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.381 inches single mounting facility single center group and 1.401 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.660 inches single mounting facility single center group and 0.680 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Open delta-wye

#### Winding Shielding Method:

Core grounded single component

#### **Body Length:**

2.320 inches

#### **Body Width:**

2.020 inches

## **Body Height:**

1.620 inches

## **Maximum Operating Temp:**

155.0 degrees celsius

#### **End Application:**

Lantirn target prodject

## **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

## **Thread Size:**

0.138 inches single group

#### **Winding Operating Current:**

10.0 amperes ac single component single secondary

## **Winding Operating Voltage:**

6.90 ac volts single component single secondary

## **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

9 tab, solder lug

# NSN 5950-01-292-3379

Power Transformer - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0