## NSN 5950-01-292-8178

Current Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-292-8178   |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 2.690 inches single mounting facility single center group and 2.710 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.780 inches single mounting facility single center group and 1.800 inches single mounting facility single center group |
| Mounting Slot Width:  |
| 0.200 inches single group and 0.220 inches single group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Body Length:  |
| Between 3.470 inches and 3.530 inches   |
| Body Width:   |
| Between 1.100 inches and 1.160 inches   |
| Body Height:  |
| Between 3.600 inches and 3.660 inches   |
| End Application:  |
| Radar set   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Slot single group   |
| Winding Function And Quantity:  |
| 1 secondary single component  |
| Winding Operating Current:  |
| 500.0 amperes ac single component single primary  |
| Special Features:   |
| Primary rated but not included  |
| Terminal Type And Quantity:   |
| 2 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

A058b0