NSN 5950-01-292-9144

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-292-9144

| Rε | lia | ıbil | ity | Ind | icato | r: |
|----|-----|------|-----|-----|-------|----|
| | | | | | | |

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.199 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.120 inches

Body Width:

2.620 inches

Body Height:

1.950 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Winding Operating Current:

3.0 amperes ac single component 2nd secondary

Winding Operating Voltage:

9.00 ac volts single component 3rd secondary

Terminal Type And Quantity:

22 tab, solder lug

Specification Data:

00752-431111 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-01-292-9144

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0