

View Online at <https://aerobasegroup.com/nsn/5950-01-293-1090>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.678 inches single mounting facility single center group and 3.698 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

300.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 4.563 inches and 4.688 inches

Body Width:

Between 3.875 inches and 4.000 inches

Body Height:

Between 4.750 inches and 4.938 inches

Maximum Operating Temp:

130.0 degrees celsius

End Application:

Countermeasures set

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

682.0 milliamperes ac single component single primary

Winding Power Rating:

252.0 volts-amperes single component single secondary

Winding Operating Voltage:

440.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0