NSN 5950-01-293-9745

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-293-9745

| Poliability Indicator: |
|---|
| Reliability Indicator: Not established |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.625 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz single component or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.562 inches |
| Body Width: |
| 3.062 inches |
| Body Height: |
| 3.875 inches |
| End Application: |
| Airport surveillance radar (asr-9); next generation radar (nexrad) |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Winding Operating Current: |
| 0.010 amperes ac single component single primary |
| Winding Operating Voltage: |
| 120.00 ac volts single component single primary |
| Special Features: |
| Nsn restricted to use by nws depot team only |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 2 standoff, screw and 2 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-01-293-9745

Power Transformer - Page 2 of 2



Fiig:

A058b0