# NSN 5950-01-294-1464

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-294-1464

# **Reliability Indicator:**

Not established

# Inductance Rating:

125.00 millihenries single component single secondary

# Frequency Rating:

27.0 kilohertz single component and 33.0 kilohertz single component

# Winding Shielding Method:

Internal shield brought out to terminal single component

## **Body Length:**

1.130 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

# Maximum Operating Temp:

170.0 degrees celsius

# Distance Between Mounting Facility Centers:

0.740 inches single mounting facility single center group and 0.760 inches single mounting facility single center group

## Inclosure Type:

Fully enclosed

## Mounting Facility Quantity:

2 single group

#### Mounting Method:

Threaded hole single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Thread Size:

0.112 inches single group

## Winding Operating Current:

7.07 amperes ac single component single primary

#### Dc Resistance Rating In Ohms:

52.000 single component single secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

5 turret

Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5950-01-294-1464

Pulse Transformer - Page 2 of 2

**Fiig:** A058b0

