## NSN 5950-01-294-1464

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-294-1464 **Reliability Indicator:** Not established **Inductance Rating:** 125.00 millihenries single component single secondary Frequency Rating: 27.0 kilohertz single component and 33.0 kilohertz single component Winding Shielding Method: Internal shield brought out to terminal single component **Body Length:** 1.130 inches **Body Width:** 0.500 inches **Body Height:** 0.500 inches **Maximum Operating Temp:** 170.0 degrees celsius **Distance Between Mounting Facility Centers:** 0.740 inches single mounting facility single center group and 0.760 inches single mounting facility single center group **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 2 single group **Mounting Method:** Threaded hole single group **Winding Function And Quantity:** 1 primary single component and 1 secondary single component **Thread Size:** 0.112 inches single group **Winding Operating Current:** 7.07 amperes ac single component single primary Dc Resistance Rating In Ohms: 52.000 single component single secondary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 5 turret Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5950-01-294-1464

Pulse Transformer - Page 2 of 2



Fiig:

A058b0