

View Online at <https://aerobasegroup.com/nsn/5950-01-294-5785>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Salt spray resistant and vibration resistant and humidity resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.980 inches single mounting facility single center group and 1.020 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.600 inches single mounting facility single center group and 0.640 inches single mounting facility single center group

**Overall Height:**

1.250 inches

**Inductance Rating:**

1.80 millihenries single component single primary

**Frequency Rating:**

30.0 kilohertz single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

1.400 inches

**Body Width:**

1.000 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

325.0 milliamperes ac single component single primary

**Dc Resistance Rating In Ohms:**

2.500 single component single primary

**Winding Operating Voltage:**

9.19 ac volts single component 4th secondary

**Special Features:**

One primary winding; 6 secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

17 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A058b0