

View Online at <https://aerobasegroup.com/nsn/5950-01-294-5785>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Salt spray resistant and vibration resistant and humidity resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.980 inches single mounting facility single center group and 1.020 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.600 inches single mounting facility single center group and 0.640 inches single mounting facility single center group

Overall Height:

1.250 inches

Inductance Rating:

1.80 millihenries single component single primary

Frequency Rating:

30.0 kilohertz single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.400 inches

Body Width:

1.000 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

325.0 milliamperes ac single component single primary

Dc Resistance Rating In Ohms:

2.500 single component single primary

Winding Operating Voltage:

9.19 ac volts single component 4th secondary

Special Features:

One primary winding; 6 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0