# NSN 5950-01-294-5787

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-294-5787

Reliability	Indicator:
-------------	------------

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.094 inches single mounting facility single center group and 2.156 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.344 inches single mounting facility single center group and 1.406 inches single mounting facility single center group

#### **Inductance Type:**

Swinging

#### **Inductance Rating:**

1.00 henry single component single winding

#### Frequency Rating:

2.4 kilohertz single component

#### **Body Length:**

2.750 inches

#### **Body Width:**

2.375 inches

#### **Body Height:**

3.812 inches

#### **Maximum Operating Temp:**

130.0 degrees celsius

#### Winding Quantity:

1 single component

#### **Inclosure Type:**

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

### Rating Method:

Electrical single component single winding

#### **Thread Size:**

0.138 inches single group

#### **Winding Operating Current:**

90.0 milliamperes dc single component single winding and 140.0 milliamperes dc single component single winding

## Dc Resistance Rating In Ohms:

100.000 single component single winding

#### **Special Features:**

Internal shield grounded to inclosure

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

2 turret

# NSN 5950-01-294-5787

Reactor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0