## NSN 5950-01-294-6682

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-294-6682

view Online at https://aerobasegroup.com/nsn/3330-01-234-0002
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Salt spray resistant and vibration resistant and humidity resistant
Frequency Rating:
1.0 kilohertz single component
nput-output Phase Relationship:
Single phase to single phase single component
Body Length:
1.360 inches
Body Width:
1.360 inches
Body Height:
0.520 inches
Maximum Operating Temp:
35.0 degrees celsius
Distance Between Mounting Facility Centers:
0.980 inches single mounting facility single center group and 1.020 inches single mounting facility single center group
nclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 secondary single component
Thread Size:
0.112 inches single group
Winding Operating Current:
28.3 amperes ac single component all primary
Special Features:
Primaries rated but not included; terminals 3 and 5 internally connected by wire
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
5 turret
Specification Data:
53711-6127554 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-294-6682

Current Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0