

View Online at <https://aerobasegroup.com/nsn/5950-01-294-6687>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.400 inches single mounting facility single center group and 6.600 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.490 inches single mounting facility single center group and 2.510 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

400.0 volt-ampere single component

Body Length:

7.880 inches

Body Width:

4.500 inches

Body Height:

6.300 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.312 inches single group

Winding Operating Current:

75.0 milliamperes dc single component 2nd secondary and 750.0 milliamperes dc single component 2nd secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

40.00 dc volts single component 4th secondary

Special Features:

Item must comply with requirements of desc production standard no. L04054; for navy nuclear propulsion plant products only; one primary winding; 5 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0