## NSN 5950-01-294-6687

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-294-6687

Reliability	Indicator:
-------------	------------

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

6.400 inches single mounting facility single center group and 6.600 inches single mounting facility single center group

## **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.490 inches single mounting facility single center group and 2.510 inches single mounting facility single center group

## Frequency Rating:

60.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

## **Maximum Transformer Power Rating:**

400.0 volt-ampere single component

**Body Length:** 

**7.880** inches

**Body Width:** 

4.500 inches

**Body Height:** 

6.300 inches

## **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

## **Winding Function And Quantity:**

1 primary single component and 5 secondary single component

## Thread Size:

0.312 inches single group

#### **Winding Operating Current:**

75.0 milliamperes dc single component 2nd secondary and 750.0 milliamperes dc single component 2nd secondary

## **Criticality Code Justification:**

Feat

## **Winding Operating Voltage:**

40.00 dc volts single component 4th secondary

## **Special Features:**

Item must comply with requirements of desc production standard no. L04054; for navy nuclear propulsion plant products only; one primary winding; 5 secondary windings

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

13 pin

## Shelf Life:

N/a

# NSN 5950-01-294-6687

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0