

View Online at <https://aerobasegroup.com/nsn/5950-01-294-7642>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.359 inches single mounting facility single center group and 1.391 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.234 inches single mounting facility single center group and 1.266 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

1.938 inches

Body Width:

1.812 inches

Body Height:

2.438 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

45.0 milliamperes ac single component single secondary

Winding Power Rating:

16.2 volts-amperes single component single secondary

Winding Operating Voltage:

85.00 ac volts single component single primary and 93.50 ac volts single component single primary and 102.00 ac volts single component single primary and 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Specification Data:

10001-2903456 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0