

View Online at <https://aerobasegroup.com/nsn/5950-01-294-8347>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.950 inches single mounting facility single center group and 0.970 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.890 inches single mounting facility single center group and 0.910 inches single mounting facility single center group

Mounting Hole Diameter:

0.146 inches single group and 0.166 inches single group

Frequency Rating:

100.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.310 inches

Body Width:

1.250 inches

Body Height:

0.810 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.00 amperes ac single component single secondary

Winding Operating Voltage:

53.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0