## NSN 5950-01-294-8348

Power Transformer - Page 1 of 1



facility single center group

facility single center group

view Online at https://aerobasegroup.com/hsh/5950-01-294-6546
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.950 inches single mounting facility single center group and 0.970 inches single mounting
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.890 inches single mounting facility single center group and 0.910 inches single mounting
Mounting Hole Diameter:
0.146 inches single group and 0.166 inches single group
Frequency Rating:
100.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
1.310 inches
Body Width:
1.250 inches
Body Height:
0.810 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
4.0 amperes ac single component single secondary
Winding Operating Voltage:
55.00 ac pounds per hour wet single component single primary
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

A058b0