

View Online at <https://aerobasegroup.com/nsn/5950-01-294-9559>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.969 inches single mounting facility single center group and 5.031 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.563 inches single mounting facility single center group and 4.687 inches single mounting facility single center group

Mounting Slot Width:

0.260 inches single group and 0.300 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye and delta-delta

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to terminal single component

Body Length:

8.000 inches

Body Width:

5.880 inches

Body Height:

6.750 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

9.8 amperes ac single component 4th secondary

Winding Operating Voltage:

20.80 ac volts single component 4th secondary

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0