## NSN 5950-01-294-9559

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-294-9559

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.969 inches single mounting facility single center group and 5.031 inches single mounting facility single center group

## **Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.563 inches single mounting facility single center group and 4.687 inches single mounting facility single center group

#### **Mounting Slot Width:**

0.260 inches single group and 0.300 inches single group

#### **Frequency Rating:**

60.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-wye and delta-delta

#### Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to terminal single component

#### **Body Length:**

8.000 inches

#### **Body Width:**

5.880 inches

## **Body Height:**

6.750 inches

#### **Maximum Operating Temp:**

170.0 degrees celsius

## **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Slot single group

## Winding Function And Quantity:

1 primary single component and 4 secondary single component

#### **Winding Operating Current:**

9.8 amperes ac single component 4th secondary

#### **Winding Operating Voltage:**

20.80 ac volts single component 4th secondary

## **Terminal Type And Quantity:**

17 tab, solder lug

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-01-294-9559

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0