

View Online at <https://aerobasegroup.com/nsn/5950-01-297-8517>

Reliability Indicator:

Not established

Impedance Rating In Ohms:

3000.0 single component all primary

Frequency Rating:

1.0 megahertz single component

Primary To Secondary Turn Ratio:

1 to 1-7/16 single component

Body Length:

1.700 inches

Body Width:

1.500 inches

Body Height:

0.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

3 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

4 primary single component and 4 secondary single component

Features Provided:

W/resistor

Thread Size:

0.138 inches single group

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

0.890 inches single mounting facility single center group and 0.910 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group

Test Data Document:

81755-c8839 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0