## NSN 5950-01-299-1276

Power Transformer - Page 1 of 1

Fiig:



View Online at https://aerobasegroup.com/nsn/5950-01-299-1276

Reliability Indicator:
Not established
Overall Length:
8.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.375 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
5.750 inches single mounting facility single center group
Overall Height:
6.250 inches
Overall Width:
6.750 inches
Mounting Slot Width:
0.438 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Transformer Power Rating:
1000.0 volt-ampere single component
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Bracket single group and slot single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
1.6 amperes ac single component single secondary and 10.1 amperes ac single component single secondary
Winding Operating Voltage:
85.00 ac volts single component single secondary or 91.00 ac volts single component single secondary or 95.00 ac volts single component
single secondary or 99.00 ac volts single component single secondary and 100.00 ac volts single component single secondary or 110.00 ac
volts single component single secondary or 115.00 ac volts single component single secondary or 120.00 ac volts single component single
secondary and 125.00 ac volts single component single secondary or 130.00 ac volts single component single secondary
Terminal Type And Quantity:
9 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No