NSN 5950-01-300-9011

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-300-9011

| Reliability Indicator: |
|---|
| Not established |
| Hazardous Locations/environmental Protection: |
| Vibration resistant |
| Overall Length: |
| 1.420 inches |
| Overall Height: |
| 0.550 inches |
| Overall Width: |
| 0.570 inches |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 67.50 microhenries single component all winding and 90.00 microhenries single component all winding |
| Frequency Rating: |
| 20.0 kilohertz single component |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Winding Quantity: |
| 4 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Terminal single group |
| Rating Method: |
| Electrical single component all winding |
| Features Provided: |
| Tinned wire leads |
| Winding Operating Current: |
| 750.0 milliamperes dc single component all winding |
| Dc Resistance Rating In Ohms: |
| 0.150 single component all winding |
| Terminal Type And Quantity: |
| 8 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |