

View Online at <https://aerobasegroup.com/nsn/5950-01-301-9807>

Reliability Indicator:

Not established

Overall Length:

0.370 inches

Impedance Rating In Ohms:

500.0 single component single primary

Frequency Rating:

400.0 hertz single component and 250.0 kilohertz single component

Maximum Transformer Power Rating:

1.0 milliwatts single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Overall Diameter:

0.350 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

2.0 milliamperes dc single component single primary

Precious Material And Location:

Plated terminals gold

Precious Material:

Gold

Test Data Document:

80064-2618756 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0