

View Online at <https://aerobasegroup.com/nsn/5950-01-302-3326>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.735 inches single mounting facility single center group and 2.765 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.110 inches single mounting facility single center group and 2.140 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 3.720 inches and 3.780 inches

Body Width:

Between 2.970 inches and 3.030 inches

Body Height:

Between 3.220 inches and 3.280 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

2.5 amperes dc single component single secondary

Winding Operating Voltage:

150.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0