

View Online at <https://aerobasegroup.com/nsn/5950-01-302-3330>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.940 inches 1st mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.790 inches 1st mounting facility single center group

Mounting Hole Diameter:

0.191 inches 1st group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-wye

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.570 inches

Body Width:

2.320 inches

Body Height:

3.980 inches

Maximum Operating Temp:

70.0 degrees celsius

End Application:

F-16 adf radar

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 1st group

Mounting Method:

Unthreaded hole all groupings

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

1.570 inches 2nd mounting facility single center group

Winding Operating Current:

91.0 milliamperes ac single component 2nd secondary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.350 inches 2nd mounting facility single center group

Winding Operating Voltage:

200.00 ac pounds per hour wet single component single primary

Test Data Document:

97942-593r819 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

24 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0