

View Online at <https://aerobasegroup.com/nsn/5950-01-302-6000>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.282 inches single mounting facility single center group and 3.342 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.032 inches single mounting facility single center group and 4.092 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

600.0 volt-ampere single component

Body Length:

Between 5.690 inches and 5.810 inches

Body Width:

Between 7.440 inches and 7.560 inches

Body Height:

Between 4.940 inches and 5.060 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Operating Voltage:

95.00 ac volts single component single primary and 105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary

Special Features:

Terminal number 8, is not used

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0