

View Online at <https://aerobasegroup.com/nsn/5950-01-302-6000>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.282 inches single mounting facility single center group and 3.342 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.032 inches single mounting facility single center group and 4.092 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

600.0 volt-ampere single component

**Body Length:**

Between 5.690 inches and 5.810 inches

**Body Width:**

Between 7.440 inches and 7.560 inches

**Body Height:**

Between 4.940 inches and 5.060 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

20.0 amperes ac single component single secondary

**Winding Operating Voltage:**

95.00 ac volts single component single primary and 105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary

**Special Features:**

Terminal number 8, is not used

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0