

View Online at <https://aerobasegroup.com/nsn/5950-01-303-3507>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

0.920 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.734 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.440 inches single mounting facility single center group

Overall Height:

1.010 inches

Overall Width:

0.620 inches

Mounting Hole Diameter:

0.104 inches single group

Inductance Type:

Fixed

Inductance Rating:

80.00 microhenries single component single winding

Frequency Rating:

20.0 kilohertz single component

Maximum Operating Temp:

155.0 degrees celsius

End Application:

7010-01-017-7039, fire direction center

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

5.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.050 single component single winding

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 turret

Specification Data:

81349-mil-t-27/282 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0