NSN 5950-01-305-2969

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-305-2969

Reliability Indicator:

Not established

Turn Quantity:

22 single component all winding

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Inductance Rating:

94.00 microhenries single component all winding

Frequency Rating:

10.0 kilohertz single component

Body Length:

Between 2.045 inches and 2.055 inches

Body Width:

Between 1.545 inches and 1.555 inches

Body Height:

Between 1.445 inches and 1.455 inches

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component all winding and winding turns single component all winding

Thread Size:

0.112 inches single group

Winding Conductor Size:

0.04030 inches american wire gage single component all winding

Winding Operating Current:

3.94 amperes dc single component all winding

Dc Resistance Rating In Ohms:

38.000 single component all winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

NSN 5950-01-305-2969

Reactor - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0