NSN 5950-01-305-3187

Power Transformer - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5950-01-305-3187

Reliability Indicator: Not established Overall Length: 4.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.250 inches 2nd mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.375 inches 2nd mounting facility single center group Overall Height: 3.225 inches Overall Width: 2.3125 inches Overall Width: 2.3125 inches Overall Width: 2.3126 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Facility Quantity: 4 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Ferminal Type And Quantity: 21 wire lead	
Overall Length: 4.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.250 inches 2nd mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.375 inches 2nd mounting facility single center group Overall Height: 3.225 inches Overall Width: 2.3125 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to inthee phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Winding Facility Quantity: 1 primary single component and 7 secondary single component Thready day Per Inch (trpl): 32 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Steps Designator: Unc 1st group Tennal Type And Quantity:	Reliability Indicator:
4.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.250 inches 2nd mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.375 inches 2nd mounting facility single center group Overall Height: 3.225 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: 0.1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thread Qty Per Inch (tpl): 32 1st group Winding Operating Current: 3.5.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 4 15.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Templal Type And Quantity:	Not established
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.250 inches 2nd mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.375 inches 2nd mounting facility single center group Overall Height: 2.325 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 1.00.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Facility Quantity: 1 primary single component and 7 secondary single component Thread Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Stries Designator: Unc 1st group Thread Stries Designator: Unc 1st group	Overall Length:
1.250 inches 2nd mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.375 inches 2nd mounting facility single center group Overall Height: 3.225 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	4.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.375 inches 2nd mounting facility single center group Overall Height: 3.225 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qny Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches 2nd mounting facility single center group Overall Height: 3.225 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Treval Series Designator: Unc 1st group Terminal Type And Quantity:	1.250 inches 2nd mounting facility single center group
Overall Height: 3.225 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thread Yte Pr Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Treminal Type And Quantity:	Center To Center Distance Between Mounting Facilities Parallel To Width:
3.225 inches Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thread Yer P Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	2.375 inches 2nd mounting facility single center group
Overall Width: 2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Overall Height:
2.3125 inches Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	3.225 inches
Mounting Hole Diameter: 0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: C1 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Overall Width:
0.156 inches 2nd group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	2.3125 inches
Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Mounting Hole Diameter:
400.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	0.156 inches 2nd group
Input-output Phase Relationship: Three phase to three phase single component End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Frequency Rating:
Three phase to three phase single component End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	400.0 hertz single component
End Application: Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Input-output Phase Relationship:
Ct 2 multimode radar Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Three phase to three phase single component
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	End Application:
Fully enclosed Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Ct 2 multimode radar
Mounting Facility Quantity: 4 2nd group Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Inclosure Type:
Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Fully enclosed
Mounting Method: Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Mounting Facility Quantity:
Unthreaded hole 2nd group Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	4 2nd group
Winding Function And Quantity: 1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Mounting Method:
1 primary single component and 7 secondary single component Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Unthreaded hole 2nd group
Thready Qty Per Inch (tpi): 32 1st group Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Winding Function And Quantity:
Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	1 primary single component and 7 secondary single component
Thread Size: 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Thready Qty Per Inch (tpi):
 0.190 inches 1st group Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity: 	32 1st group
Winding Operating Current: 35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Thread Size:
35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	0.190 inches 1st group
Winding Operating Voltage: 45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Winding Operating Current:
45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary Thread Series Designator: Unc 1st group Terminal Type And Quantity:	35.0 milliamperes ac single component 1st secondary and 165.0 milliamperes ac single component 1st secondary
Thread Series Designator: Unc 1st group Terminal Type And Quantity:	Winding Operating Voltage:
Unc 1st group Terminal Type And Quantity:	45.90 ac volts single component 1st secondary and 50.20 ac volts single component 1st secondary
Terminal Type And Quantity:	Thread Series Designator:
	Unc 1st group
21 wire lead	Terminal Type And Quantity:
	21 wire lead
Shelf Life:	Shelf Life:

NSN 5950-01-305-3187

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0