

View Online at <https://aerobasegroup.com/nsn/5950-01-306-8826>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.395 inches single mounting facility single center group and 1.405 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.395 inches single mounting facility single center group and 1.405 inches single mounting facility single center group

Overall Height:

1.650 inches

Frequency Rating:

167.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 1.770 inches and 1.830 inches

Body Width:

Between 1.770 inches and 1.830 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

1.3 amperes ac single component all secondary

Winding Operating Voltage:

49.20 ac volts single component all secondary

Test Data Document:

04939-717801562 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0