NSN 5950-01-306-9085

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-306-9085

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.955 inches single mounting facility single center group and 0.965 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.890 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.009 inches single group and 0.019 inches single group |
| Frequency Rating: |
| 10.0 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 1.980 inches |
| Body Width: |
| 1.660 inches |
| Body Height: |
| 2.970 inches |
| Maximum Operating Temp: |
| 71.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 2 primary single component and 5 secondary single component |
| Winding Operating Current: |
| 625.0 milliamperes dc single component all primary |
| Winding Operating Voltage: |
| 500.00 dc pounds per hour with retaining chain single component all secondary |
| Special Features: |
| 2 primary windings; 5 secondary windings |
| Terminal Type And Quantity: |
| 14 wire lead |
| Shelf Life: |
| N/a |
| |

--

Unit Of Measure:

NSN 5950-01-306-9085

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0