# NSN 5950-01-307-4475

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-307-4475

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.365 inches single mounting facility single center group and 1.385 inches single mounting facility single center group

## **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.240 inches single mounting facility single center group and 1.260 inches single mounting facility single center group

## **Inductance Type:**

Fixed

## **Inductance Rating:**

15.00 microhenries single component all winding

## Frequency Rating:

15.0 kilohertz single component

#### **Body Length:**

1.820 inches

## **Body Width:**

1.630 inches

## **Body Height:**

1.700 inches

# **Maximum Operating Temp:**

170.0 degrees celsius

# Winding Quantity:

2 single component

# Inclosure Type:

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded hole single group

# Rating Method:

Electrical single component all winding

## **Thread Size:**

0.112 inches single group

## **Winding Operating Current:**

60.0 amperes dc single component all winding

## Dc Resistance Rating In Ohms:

0.0016 single component all winding

## **Test Data Document:**

10001-2916252 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

4 tab, solder lug

# NSN 5950-01-307-4475

Reactor - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0