

View Online at <https://aerobasegroup.com/nsn/5950-01-307-7131>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.365 inches single mounting facility single center group and 1.385 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group

Overall Height:

2.650 inches

Frequency Rating:

15.0 kilohertz single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.880 inches

Body Width:

1.740 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

750.0 milliamperes dc single component single primary

Winding Operating Voltage:

5.30 ac volts single component single primary and 10.61 ac volts single component single primary and 106.05 ac volts single component single primary and 111.35 ac volts single component single primary and 116.66 ac volts single component single primary

Test Data Document:

10001-2916253 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0