

View Online at <https://aerobasegroup.com/nsn/5950-01-307-7609>

**Reliability Indicator:**

Not established

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

Between 1.210 inches and 1.270 inches

**Body Width:**

Between 1.210 inches and 1.270 inches

**Body Height:**

Between 0.590 inches and 0.650 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Distance Between Mounting Facility Centers:**

0.958 inches single mounting facility single center group and 0.978 inches single mounting facility single center group

**Mounting Tab Width:**

0.032 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Tab single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Winding Operating Current:**

330.0 milliamperes ac single component all secondary

**Winding Operating Voltage:**

6.00 ac volts single component all secondary and 9.00 ac volts single component all secondary and 15.00 ac volts single component all secondary

**Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 pin

**Specification Data:**

81349-mil-t-27/325 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0