

View Online at <https://aerobasegroup.com/nsn/5950-01-307-7609>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 1.210 inches and 1.270 inches

Body Width:

Between 1.210 inches and 1.270 inches

Body Height:

Between 0.590 inches and 0.650 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

0.958 inches single mounting facility single center group and 0.978 inches single mounting facility single center group

Mounting Tab Width:

0.032 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Tab single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

330.0 milliamperes ac single component all secondary

Winding Operating Voltage:

6.00 ac volts single component all secondary and 9.00 ac volts single component all secondary and 15.00 ac volts single component all secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin

Specification Data:

81349-mil-t-27/325 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0