

View Online at <https://aerobasegroup.com/nsn/5950-01-309-4081>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.945 inches single mounting facility single center group and 1.955 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.945 inches single mounting facility single center group and 1.955 inches single mounting facility single center group

Frequency Rating:

67.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 2.230 inches and 2.270 inches

Body Width:

Between 2.230 inches and 2.270 inches

Body Height:

Between 1.445 inches and 1.455 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

4.5 amperes ac single component 1st secondary

Winding Operating Voltage:

37.58 ac volts single component 2nd secondary

Special Features:

Terminals 3 and 3a are connected; terminals 5 and 5a are connected; terminals 6 and 6a are connected; terminals 8 and 8a are connected

Test Data Document:

04939-717601563 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0