NSN 5950-01-309-4883

Reactor - Page 1 of 2

No



| View Online at https://aerobasegroup.com/nsn/5950-01-309-4883 |
|---|
| Reliability Indicator: |
| Not established |
| Hazardous Locations/environmental Protection: |
| Vibration resistant |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 100.00 microhenries single component all winding |
| Frequency Rating: |
| 10.0 kilohertz single component |
| Body Length: |
| 0.280 inches |
| Overall Diameter: |
| 0.410 inches |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Winding Quantity: |
| 2 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Terminal single group |
| Rating Method: |
| Electrical single component all winding |
| Winding Operating Current: |
| 780.0 milliamperes dc single component all winding |
| Dc Resistance Rating In Ohms: |
| 0.300 single component all winding |
| Special Features: |
| Magnetically shielded |
| Test Data Document: |
| 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 4 wire lead |
| Specification Data: |
| 81349-mil-t-27/356 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5950-01-309-4883

Reactor - Page 2 of 2



Fiig:

A058b0