## NSN 5950-01-310-1938

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-310-1938
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.146 inches single group and 0.166 inches single group
Inductance Type:
Fixed
Inductance Rating:
80.00 microhenries single component 1st winding
Frequency Rating:
10.0 kilohertz single component
Body Length:
Between 0.625 inches and 0.751 inches
Body Outside Diameter:
Between 1.125 inches and 1.251 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
2 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component all winding
Winding Operating Current:
7.5 amperes dc single component 1st winding
Dc Resistance Rating In Ohms:
0.032 single component 1st winding
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 pin
Specification Data:
81349-mil-t-27/288 government specification
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5950-01-310-1938

Reactor - Page 2 of 2



Fiig:

A058b0