NSN 5950-01-310-9580

Power Transformer - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-01-310-9580

Not established						
Overall Length:						
6.500 inches						
Center To Center Distance Between Mounting Facilities Parallel To Length:						
5.000 inches single mounting facility single center group						
Center To Center Distance Between Mounting Facilities Parallel To Width:						
2.500 inches single mounting facility single center group						
Overall Height:						
6.310 inches						
Overall Width:						
3.690 inches						
Frequency Rating:						
400.0 hertz single component						
Input-output Phase Relationship:						
Three phase to single phase single component and three phase to three phase single component						
Transformer Winding Connection Type:						
Wye-delta and wye-wye or delta-delta and delta-wye						
Winding Shielding Method:						
Internal shield grounded to core and brought out to terminal single component						
Maximum Operating Temp:						
85.0 degrees celsius						
Inclosure Type:						
Hermetically sealed						
Mounting Facility Quantity:						
4 single group						
Mounting Method:						
Threaded stud single group						
Winding Function And Quantity:						
1 primary single component and 8 secondary single component						
Features Provided:						
W/rectifier						
Thread Size:						
0.250 inches single group						
Winding Operating Current:						
3.0 amperes dc single component 1st secondary						
Winding Operating Voltage:						
85.00 ac volts single component 4th secondary						

8 secondary windings; primary winding also can be connected as a delta winding

Thread Series Designator:

Unc single group

Special Features:

NSN 5950-01-310-9580

Power Transformer - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

33 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0